

# Pilot Spec



GreenFields Slide Max NF

28 230 18.1 105

## TECHNICAL DATA

T100447

Type	3/8" tufted non-filled filled synthetic grass carpet, straight stitch pattern	
Pile content	100% polyethylene monofilament, diamond shape, U.V.-resistant, 6.600/3 dTex, 365 microns 'combined' with 11.500/12 dTex polyethylene monofilaments, knit-d-knit	
Primary backing	Triple: - PP/PET Thiobac, U.V. stabilized and fibre locked fleece - fibre glass rotary weave, (weight 131 gr/m <sup>2</sup> ) - PP/PET Thiobac warp knitted, total weight 372 gr/m <sup>2</sup>	
Secondary backing	Latex compound with a base of styrene-butadiene (SBR), with drainage holes	
Pile height	28 mm	+/- 5%
Total thickness	30 mm	+/- 5%
Stitch rate per 1m (width)	105	
Stitch rate per 1m (length)	230	+/- 10%
Number of filaments/m <sup>2</sup>	± 132.300 main pile and ± 529.200 thatch pile (root)	
Pile weight	2.980 gr/m <sup>2</sup>	+/- 10%
Weight primary backing	372 gr/m <sup>2</sup>	
Weight secondary backing	1.200 gr/m <sup>2</sup>	
Total weight	4.552 gr/m <sup>2</sup>	+/- 10%
Roll width	according to seaming plan	+/- 2cm
Roll length	according to seaming plan	
Tuft bind	≥ 40 Newton	
Water permeability	≥ 500mm/h	
Color Fastness	Xenon test : blue-scale>7, grey-scale>4	

Version 1, 06-01-2020

## COLOUR

Field green main pile and Field green/olive green thatch pile (root).

### INSTALLATION INSTRUCTION:

This product should be stored, handled and installed in accordance with the installation manual, ask our sales representatives for the latest version



All data shown are typical values based on tests believed to be reliable by TenCate. All technical data provided herein are subject to change without prior notification. TenCate assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by TenCate. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.